

EXHIBIT A -
 SUMMIT COUNTY ENVIRONMENT
 28' ALUMINUM FRAME DUMP TRAILER

2014-287

ITEM	SPECIFICATION	MARK COMPLY OR EXCEPTION
BIDDER INSTRUCTIONS	1) Vendors must mark COMPLY or EXCEPTION in the column to the right. Any specification marked as comply must meet the specification 100%, if You cannot comply, mark exception and state what the exception is. 2) All vendors must submit the manufacturer's name and model, along with supporting documentation for all major components being bid. 3) Bid prices and delivery promise must be entered on the price page.	
	BODY SPECIFICATIONS	
NUMBER OF UNITS	ALL COMPONENTS AND MACHINES SHALL BE NEW, CURRENTLY ADVERTISED PRODUCTION MODEL.	
LENGTH	28'	
WIDTH	96"	
TOP RAIL	4.5"	
SIDE MATERIAL	3/16"	
FLOOR MATERIAL	1/4" Full Length	
CRSMBR SPACING	12"	
FLOOR OPTIONS	Durapro 3/8" Liner or equivalent	
TAILGATE CONTROL	Air Frame Switch and plumb a line up to the front of the trailer for future use for cab control.	
TARP	Cable Tarp shall be Electric front to Back with Bows to hold the Tarp up in middle and switch on the front of the trailer and plumb for future use for cab control	

SUMMIT COUNTY ENVIRONMENT
28' ALUMINUM FRAME DUMP TRAILER

BULKHEAD	Bulkhead shall have 1/4" Aluminum on it and a 5" slope plate to help slow down material hitting the bulkhead, with a Sealed Man Door.	
DOG HOUSE	With 3/8" Aluminum	
BOTTOM RAIL	5" Aluminum for easy clean out and to help reinforce the welds to the bottom and side of the trailer.	
BODY FENDERS	18" Diamond Plate	
MUDFLAPS	All across the rear of the Trailer	
LADDERS	(Out) D.S. First and last panels (Inside) D.S. first panels	
SHOVEL HGR	Outside P.S. Bulkhead	
DIRTSHEDDERS	Diamond Plate	
LIGHT PANEL	OOO ooo OOO The back Lights shall have LED lights	
MARKER LIGHTS	3 Per Side and Marker Lights shall have LED lights, MMTS Box in Below Rail	
TAILGATE	Height of the Tailgate shall be Full, Thickness of the Tailgate to be 3/16". Hinges Overslung and Side Swing into ground control, controlled from the ground. With a Gate Seal	
ITEM	CHASSIS SPECIFICATIONS	MARK COMPLY OR EXCEPTION
MODEL	Tandem and lift	
BEAM MATERIAL	Aluminum	
LENGTH	29'	

SUMMIT COUNTY ENVIRONMENT
28' ALUMINUM FRAME DUMP TRAILER

WIDTH	96"	
HOIST	8-5-235	
CHASSIS NECK	Fit a Tandem Truck	
KING PIN SETTING	18"	
5 TH WHEEL PLATE	5/16"	
5 th WHEEL HEIGHT	49"	
OVERHANG	6"	
REAR AXLE SETTING	21.5"	
KINGPIN TO REAR AXLE	308.5'	
SUSPENSION	AAT30K/E2-1 or equivalent, Suspension Control Switch on the Frame and ran up to the front of the trailer to be controlled from the tractor. Suspension spacing 52"	
SPRINGS	Air Bags	
AXLES (2)	Integrated, With LWBD Drum Brakes 16.5 x 7, 10 S-LWSTEEL Hubs or equivalent, 4S-2M ABS	
INDEPEND SUSPENSION	Hendrickson Composolite FX 13K GAWR, 52" from Adjacent Axle	
WHEELS & TIRES	8.25 x 22.5 Aluminum Disc Rim with a clean buff, R196 11R x 22.5	
LANDING GEAR	JOST A440 MAG, D.S Crank	

SUMMIT COUNTY ENVIRONMENT
28' ALUMINUM FRAME DUMP TRAILER

ELECTRIC COUPLER	7 Way	
HYDRAULIC HOSE FITTING	Wingnut	
HYDRAULIC HOSE LENGTH	108"	
TOW HOOKS	Two (2) on each side in the back of the frame, painted black	
TARP BAR TAPE	Black	